

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number
WO 2004/005946 A3

(51) International Patent Classification⁷: **G01R 31/3185**,
31/316

Eindhoven (NL). **DE JONG, Franciscus, G., M.** [NL/NL];
c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number:
PCT/IB2003/002957

(74) Agent: **DUIJVESTIJN, Adrianus, J.**; Philips Intellectual
Property & Standards, Prof. Holstlaan 6, NL-5656 AA
Eindhoven (NL).

(22) International Filing Date: 20 June 2003 (20.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02077733.0 8 July 2002 (08.07.2002) EP

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG,
US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **KONIN-
KLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **VAN DE LOGT,
Leon, M., A.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA

[Continued on next page]

(54) Title: **ELECTRONIC CIRCUIT WITH TEST UNIT FOR TESTING INTERCONNECTS**



(57) **Abstract:** A test arrangement for testing the interconnections of an electronic circuit (100) and a further electronic circuit is provided. A first selection of I/O nodes (120), which are arranged to receive input data in a functional mode of the electronic circuit (100), and which are coupled to a test unit in a test mode of the electronic circuit (100). The test unit has a combinatorial circuit (160) for implementing a multiple-input XOR or XNOR gate. The test unit also provides interconnections between the first selection of I/O nodes (120) and a second selection of I/O nodes (130) via logic gates (141-144). These interconnections increase the interconnect test coverage of the electronic device (100), because the interconnects with the further electronic circuits that are associated with I/O nodes (131-134) become testable as well.